

AHC-16-860

Active Combiner



AHC-16-860 SPECIFICATIONS:

Frequency Range:	54-860 MHz
Gain (dB):	12dB (adjustable)
Port to Port Isolation:	40dB (typical)
Maximum Input Level:	42dB (16 Channels)
Input Return Loss:	16 dB (typical)
Output Return Loss:	16 dB (typical)
Impedance:	75 ohm
Power Requirements:	117 VAC @ 60 Hz
Operating Temperature:	0° to 50° C
Dimensions:	19" L x 2 2/7" D x 1 3/4" H
Weight:	3 3/4 lbs.

Installation Instructions:

1. Plug in the AHC-16-860 and check for the power L.E.D. to come on.
2. Connect all modulators or processors to the input ports of the AHC-16-860.
3. Then set output level by the adjustment pot on the front of the unit.
4. Terminate all unused ports with 75ohm terminators.
5. Connect the combined output of the AHC-16-860 to distribution system.

IMPORTANT!!

WARNING: Holland Electronics does NOT represent this product to be WATERPROOFED. To reduce risk of electrical shock, fire hazard, or damage to the unit, do not expose to rain or moisture.

CAUTION: To prevent electric shock, do not use this plug with an extension cord, receptacle or other outlet unless the blades can be fully inserted to prevent blade exposure.

NOTE TO INSTALLER: This reminder calls the system installer's attention to Article 820-22 of the NEC that provides guidelines for proper grounding and, in particular, specifies that the cable ground shall be connected to the grounding system of the building, as close to the point of cable entry as practical.

**WARNING:
TO PREVENT FIRE OR ELECTRICAL SHOCK, DO NOT EXPOSE THIS UNIT TO RAIN OR
MOISTURE**



**HOLLAND ELECTRONICS LLC
LIMITED WARRANTY**

Holland ELECTRONICS LLC warrants that the product enclosed with this Limited Warranty statement will conform to the manufacturer's specifications and be free of defects in the workmanship and material for a period of five years (5) from the date of original purchase.

WARRANTY PROCEDURE:

If the product appears to be defective, contact Holland Electronics LLC at (805) 339-9060. We will analyze the problem and offer solutions to prevent removing the unit from service. If the unit is to be returned for evaluation, you will be issued a Return Material Authorization (RMA) number.

Holland Electronics LLC will, at its option, repair or replace the defective unit, under warranty, without charge for parts or labor. This repair will be subject to charges if signs of tampering or misuse are detected. Incoming shipping costs will be the customer's responsibility. Returns will not be accepted without an RMA number.

The warranty and remedy provided above are exclusive and in lieu of all other express warranties and unless stated herein, any statements or representations made by any other person or firm are void. The duration of any implied warranties of merchantability or fitness for a particular purpose on this product shall be limited to the duration of the express warranty set fourth above. Except as provided in this written warranty, Holland Electronics LLC shall not be liable for any loss, inconvenience, or damage, including direct, special, incidental, or consequential damages, resulting from the use or inability to use this product, whether resulting from breach of warranty or any other legal theory.

Some states do not allow limitations on how long an implied warranty lasts and some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation and exclusion may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

**To arrange for Warranty Service: Call Holland Electronics LLC (805) 339-9060
2935 Golf Course Dr. Ventura, Ca 93003**